

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599
www.miamidade.gov/economy

Greenheck Fan Corporation P.O. Box 410 Schofield, WI 54476

Scope:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code. This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Model ESS-502D Aluminum Louver

APPROVAL DOCUMENT: Drawing No. ESS-502D, titled "ESS-502D Louver", Sheets 1 through 16 of 16, dated 04/27/2009, prepared by Greenheck Fan Corporation, signed and sealed by Chander P. Nangia, P.E., bearing the Miami-Dade County Product Control renewal stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/series, and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official. This NOA renews NOA # 09-0519.14 and consists of this page 1 and evidence page E-1, as well as approval document mentioned above.

The submitted documentation was reviewed by Carlos M. Utrera, P.E.

MIAMIDADE COUNTY
APPROVED

Strano 109/16/2014

NOA No. 14-0624.16 Expiration Date: August 05, 2019 Approval Date: September 25, 2014

Page 1

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS "Submitted under NOA # 09-0519.14"

1. Drawing No. **ESS-502D**, titled "ESS-502D Louver", sheets 1 through 16 of 16, dated 04/27/2009, prepared by Greenheck Fan Corporation, signed and sealed by Chander P. Nangia, P.E.

B. TESTS "Submitted under NOA # 09-0519.14"

- 1. Test report on 1) Uniform Static Air Pressure Test per FBC, TAS 202-94
 - 2) Large Missile Impact Test per FBC, TAS 201-94,
 - 3) Cyclic Wind Pressure Test per FBC, TAS 203-94,

along with marked-up drawings and installation diagram of Model ESS-502D fixed aluminum louvers, prepared by Architectural Testing, Inc., Test Report No. 89882.01-602-18, dated 04/30/2009, signed and sealed by Joseph A. Reed, P.E.

C. CALCULATIONS "Submitted under NOA # 09-0519.14"

1. Structural load calculations, prepared by Greenheck Fan Corporation, dated 04/14/2009, signed and sealed by Chander P. Nangia, P.E.

D. QUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER)

E. MATERIAL CERTIFICATIONS

1. None.

F. STATEMENTS


1. Statement letter of code compliance to 2010 FBC issued by Chander P. Nangia, P.E., dated 06/19/2014, signed and sealed by Chander P. Nangia, P.E.


"Submitted under NOA # 09-0519,14"


2. No financial interest letter issued by Chander P. Nangia, P.E., dated 04/27/2009, signed and sealed by Chander P. Nangia, P.E.


Carlos M. Utrera, P.E. Product Control Examiner NOA No. 14-0624.16 Expiration Date: August 05, 2019


Approval Date: September 25, 2014
































_				
9 1	so)	ISOMETRIC	(SPLICE/STACK	DETAIL)
(9		SCALE: 1:3		

PRODUCT RENEWED
as complying with the Florida
Building Code
Acceptance No 1405416
Expiration Date 151572619
By Herry
Missni Dade Product Control

CHANDER P. NANGIA 7423 HOLLOW RIDGE DR HOUSTON, TX 77095 FLORIDA PE # 21938

 \mathcal{O} \bigcirc Ŋ DRAWN BY
NI STEELE
SCALE
VARIES
SHEET NO. DRAWING SS CAD Ш GRESNINEON P.O.BOX 410 SCHOFIELD, WISCONSIN 54476-0410 BLADE LOUVER SPLICED SUPPORT 502D ESS. DETAILS

 \odot


60/

27

MAY 1 2 2009

Approved as complying wife the Florida Building Code
Date 08/05/2009
NOA#04-05/79
Mismi Dade Product Control
Division

BELOW ARE THE SHAPE UNITS THAT THE NOA WILL ALLOW



NOTES:

- 1. OTHER SHAPES MAY APPLY PROVIDING THEY ARE SIMILAR TO THOSE SHOWN AND HAVE CONSTRUCTION AS DESCRIBED IN THIS PACKET.
- 2. ALL SHAPE LOUVERS ARE TO HAVE THE SAME WIDTH, HEIGHT, AND PRESSURE RESTRICTIONS AS RECTANGULAR LOUVERS, AND MAY BE SPLICED/STACKED VERTICALLY AND HORIZONTALLY (MULLED UNITS) IN THE SAME MANNER AS RECTANGULAR LOUVERS.
- 3. IF THE SHAPE LOUVER SECTION WIDTH EXCEEDS 72", A BLADE SUPPORT IS REQUIRED.
- 4. A MULLION REQUIRED FOR SHAPE LOUVERS ONLY IF BOTH OF THE FOLLOWING ARE TRUE: OVERALL UNIT WIDTH IS >72", AND SECTION HEIGHT IS >72".
- 5. FOLLOW THE SAME GUIDELINES AS NON-SHPAED UNITS FOR FASTENING OF SHAPE UNITS TO THE BUILDING CONDITION.

CHANDER P. NANGIA PE. 7423 HOLLOW RIDGE DR. HOUSTON, TX 77095 FLORIDA PE # 21938


PRODUCT RENEWED


502D SHAPE


CONFIGURATIONS


MAY 1 2 2009

Approved as complying with the Florida Building Code
Date 08/05/2007
NOA# 07-05/3./4
Miami Dade Broduct Control
Division By









ITEM	DESCRIPTION	MATERIAL	NOTES
1	LOUVER HEAD	ALUM	
2	LOUVER HEAD DRAIN	ALUM	
1	LDUVER BLADE	ALUM	
4A	#10 × 0.5 MIN THREAD, SCREW, 7075-T6 ALUM	ALUM	USED ON ANODIZED UNITS
1	#10 DR #12 × 0.5 MIN THREAD, SCREW, STAINLESS	22	TYPICALLY USED
5	LOUVER SILL	ALUM	
	LOUVER JAMB	ALUM	
7	DPTIONAL C-CHANNEL JAMB	ALUM	OPTIONAL FOR SHAPE UNITS
1	CONTINUOUS MTG ANGLE, 1.0×1.5×0.125 MIN, 6061-T6	ALUM	
8B	CONTINUOUS MTG ANGLE, 1.0×1.5×0.188 MIN, 6063-T5	ALUM	
9	#10-24 OR #12-24 x 0.5 MIN THREAD, SCREW	22	
10	BLADE SUPPORT CHANNEL, 2×2×2×0.25	ALUM	
11	OPTIONAL ADDITIONAL MULLION SUPPORT ANGLE	ALUM	OPTIONAL
	SLIP 'I' MULLION	ALUM	
13	GASKET, 3.5x4x0.25 MIN (BY MANUFACTURER)	VARIES	RUBBER/NEOPRENE LIKE
14	CONCRETE OR GROUT FILLED CMU, 2000 PSI MIN	VARIES	NOT BY MANUFACTURER
15	LOUVER MULLION ANGLE FOR CONCRETE/CMU	STEEL/ALUM	
16	SUBSTRATE MULLION ANGLE FOR CONCRETE/CMU	STEEL/ALUM	
17	0.25-20x1 MIN, SCREW (BY MANUFACTURER)	22	
18	BOLT, 0.5-13×1 MIN (BY MANUFACTURER)	22	
19	NUT, 0.5-13 MIN (BY MANUFACTURER)	22	
50	WASHER, 0.5 MIN (BY MANUFACTURER)	\$\$	
21	0.25 DIA. ITW BUILDEX TAPCON w/ ADV. THREADFORM, 1.75 MIN EMBEDMENT	SS/STEEL	NOT BY MANUFACTURER
55	STRUCTURAL STEEL, 0.075 MIN THICKNESS	SS/STEEL	NOT BY MANUFACTURER
23	STEEL STUD, 14GA MIN	SS/STEEL	NOT BY MANUFACTURER
24	0.25 DIAMETER SCREW, MUST FULLY ENGAGE STEEL	SS/STEEL	NOT BY MANUFACTURER
25	WOOD SUBSTRATE, G=0.55 MIN DENSITY	WOOD	NOT BY MANUFACTURER
26	MULLION ANGLE FOR WOOD	STEEL/ALUM	
	0.375 DIA. LAG SCREW, 3.0 MIN EMBEDMENT	SS/STEEL.	NOT BY MANUFACTURER
28	SPLICE CHANNEL, 2×2×2×0.25, 12" LONG	ALUM	
29	BOLT, 0.313×2.5 MIN (BY MANUFACTURER)	22	
30	NUT, 0.313(5X16) (BY MANUFACTURER)	22	
31	SPLICE PLATE	ALUM	
32	SHIMS, OPTIONAL, AS REQUIRED, INCOMPRESSABLE	VARIES	NOT BY MANUFACTURER_
33	SEALANT AND BACKER ROD	VARIES	NOT BY MANUFACTURER

GENERAL NOTES:

- 1. IT SHALL BE THE RESPONSIBILITY OF THE PERMIT HOLDER TO VERIFY THE STRUCTURAL INTEGRITY OF THE EXISTING STRUCTURE TO SUPPORT THE LOADS IMPOSED BY THE PENTHOUSE ASSEMBLY.
- 2. THE ESS-502D HAS BEEN DESIGNED AND QUALIFIED IN ACCORDANCE WITH THE FLORIDA BUILDING CODE (FBC) AND TEST PROTOCOLS TAS-201 (IMPACT), TAS-202 (UNIFORM STATIC PRESSURE), AND TAS-203 (CYCLIC FATIGUE) TO A MAXIMUM DESIGN LOAD OF +/- 110 PSF.
- 3. THE MAXIMUM UNSUPPORTED BLADE LENGTH SHALL NOT EXCEED 72" WITHOUT STIFFENER AND 144" WITH STIFFENER.
- 4. THE MAXIMUM OVERALL UNIT HEIGHT IS UNLIMITED BY MEANS OF STACKING AND USE OF SPLICED BLADE SUPPORTS. THE MAXIMUM OVERALL UNIT WIDTH IS UNLIMITED BY USE OF MULLIONS WITH A MAXIMUM SPACING OF 72".
- 5. LOUVER CONSTRUCTION: HEAD, SILL, JAMBS, AND BLADES ARE SQUARE CUT AT BOTH ENDS. BLADE SPACING IS 2" MAX. EACH JAMB IS SECURED TO THE SILL WITH (2) SCREWS AND WELDED. BLADES AND HEADS ARE SECURED TO JAMBS WITH (2) SCREWS AND WELDED.
- 6. ALL WOOD SUBSTRATE SHALL BE G = 0.55 DENSITY OR BETTER.
- 7. ALL STEEL STUD SUBSTRATE SHALL BE MIN. 14 GA. FY = 50 KSI.
- 8. ALL STRUCTURAL STEEL SUBSTRATE SHALL BE MIN. 0.075" THICK FY = 36 KSI.
- 9. ALL CONCRETE SUBSTRATE SHALL BE MIN. 2000 PSI.
- 10. CONCRETE MASONRY SHALL BE ASTM C90, TYPE II, MIN. 2000 PSI GROUT-FILLED.
- 11. THE LOUVER MANUFACTURER DOES NOT DETERMINE THE STRUCTURAL INTEGRITY OF THE SUBSTRATE STRUCTURE.
- 12. THE SYSTEM SHALL ONLY BE INSTALLED IN A LOCATION WHERE THE ENCLOSED AREA/ROOM BEHIND THE LOUVER IS DESIGNED TO DRAIN WATER PENETRATING INTO THE AREA/ROOM, AND THE AREA/ROOM WILL HOUSE WATER RESISTANT/PROOF EQUIPMENT, COMPONENTS, AND/OR SUPPLIES.
- 13. INSTALLER TO PROVIDE SEPARATION OF DISSIMILAR MATERIALS AS REQUIRED.

PRODUCT RENEWED
as consplying with the Florida
Building Code
Acceptance No 14 06 24 16
Expiration Date 08 105 17019

By
Minum Bade Product Control

CHANDER P. NANGIARE 7423 HOLLOW RIDGE DR. HOUSTON, TX 77095 FLORIDA PE # 21938

		DRAWN BY DATE
_		M SIEELE 4/2//09
	P.O.BOX 410 SCHOFIELD,	SCALE
	WISCONSIN 54476-0410	ΨZ
		SHEET NO.
SS L	FSS-502D LOUVER	(,
i I		
T C 1 / 1 / C	4 ONITOIL HOVO CHAINGE	CAD DRAWING NO.
I E INI Z E	\$ 9NII.CIJ 1884 O	
S FJ	GENERAL NOTES	ESS-SOZU



Approved as complying with the Florida Building Code
Date 08/05/2007
NOA#_19-05/7/4
Miami Dade Product Control
Division
By